

GLEAMS SPECIFICATIONS



DESCRIPTION

- Glass pieces of varying lengths make up the Gleams pendant chandelier.
- Customized dimension, shape, and finish of the ceiling plate
- Lamps can be combined in multiple configurations in which each element is positioned at different heights.
- Each light fixture is customized and made to order


GENERAL INFORMATION

SKU:	SML-1505
Collection:	GLEAMS.
Mounting	Ceiling, Chandelier
Materials:	Stained Glass, Tin canopy
UL, CSA ID	E300046-0002-C00

COMPONENTS

Pendant size	Wide: 1.8In 4.5cm. I Depth: 0.8In 2cm I Tall: 4.9In 12.5cm
Weight:	0.9lb I 0.4kg. (single pendant, including all parts)
Ceiling plate shape	Square I Round I Rectangle I triangle I ring I oval
Ceiling plate material	Tin Metal, 0.04" thick I 0.1cm
Ceiling plate size	Width + Length: Made to order I Depth: 1.575In I 4cm
Ceiling plate finish	17 options to choose from: finishes palette
Cords	Tinned copper.
Cords length	Up to 35ft long I 10m. Pre-set in cascading different lengths Adjustable
Compatible with	Slope I peaked I skylight I beam

LAMPING SPEC

Light source	Silicone LED bulb G4 
Wattage	2w (single light)
Input voltage	AC 110-240V

Lumens (single bulb)	170 lumens
Color temperature:	3000k warm white
Dimming:	Yes
Bulb included	Yes
CRI	80
Beam Angle	360°
Driver requires:	Yes, Included
Lifespan(Hrs)	20,000
Maintenance	Low, Easy to replace, Available in stores

ELECTRICAL REQUIREMENTS - INSTALLATION

Max wattage (single bulb):	2W
Voltage:	120v, 110
Location:	Dry location only
Wiring:	Single electrical outlet
Power Source:	Hardwire
Dimming:	Dimmable, any dimming switch, TRIAC included
Electrical rating:	Input: 120Vac, 60Hz, 1.3A.
Assembly Required:	No

Installation instructions:	https://did.li/XwuTY
Ceiling back plate:	https://did.li/DbJlC
UL CSA Approval:	https://did.li/2sHlC