

Cliffs **Assembly Instructions**

In the box:

- Fixture
- Glasses



Black pocket "Installation kit" contains gloves and extra ring

Keep the 'Installation Kit' until you've confirmed that all components are present.

For USA: This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

For CANADA: ce produit doit être installé selon le code d'installation pertinent, par une personne qui connaît bien le produit et son fonctionnement ainsi que les risques inhérents.

Preparation:

- 1. Determine your ceiling type (wood, drywall, or concrete) and use the appropriate screws. For drywall, locate ceiling joists and make sure the screws go beyond the drywall into the joist. For concrete, use masonry anchor screws.
- 2. Carefully pull out the fixture from the box At this stage, it's important to leave the stickers with the numbers on the plate in place. This will help you properly position the glasses later on.



Before starting installation, Turn off the relevant electrical power source to ensure safety.

4. For the next stage you will need a second person to help you hold the fixture up while you connect the electrical wire to the fixture.



Please wear the gloves provided in order to prevent leaving fingerprints on the canopy.

- 4. Connect the positive and negative wires from your elecrical box with the respective wires from the Fixture. Use the twist connector attached to the wires.
- 5. Carefully position the canopy on to the barcket and fasten it into place using the pre-exiting holes.
- 6. Before installing the glasses, make sure to verify that everything is functioning properly.

Glasses Assembly:

- 1. Carefully unpack the glasses. Each glass has a label with a number that corresponds with the number over the ceiling fixture.
- 2. To attach the glasses, insert the cable from the glass into the clips from the canopy. We recommend positioning the glasses 1-3 inches (4-7cm) from the plate. Make sure that the gap between the glasses and the canopy are equal.
- 3. The glossy side of the material faces outwards and the matte side faces inwards.



For further guidance, you can watch the instructional video by scanning the QR code provided.

Adjustment :

- 1. In case of an uneven ceiling, use white or clear silicone to bridge any space between the ceiling and canopy.
- 2. If your fixture has a double canopy, repeat the installation process for both the upper and lower canopy.

Maintenance and Care

- 1. These Led bulbs are dimmable, with any dimming switch system.
- **2. Dust:** Use a soft, dry cloth to regularly dust your fixture.
- **3. Metal:** Wipe with a damp mat.

nstallati

- 1. Detach the metal bracket from the back of the canopy and mount it onto the ceiling, with the flat side upward. Make sure the electrical wires are exposed near the bracket.
- 2. If this fixture has a double canopy-do it with the smaller one.
- 3. Twist the GND wire coming out of your electrical box with the GND wire of the light fixture. Use the twist



connector attached to the GND wire of the Lighting Fixture in order to connect between these 2 wires. >>

Note for Future: This fixture incorporates LED GU10 7w 570 lumens 3000K). Always replace with an identical bulb for consistency in performance.

ENJOY!

WhatsApp: +972-52-5279674 • Email: miri@shimale.co.il www.shimale.co.il • www.etsy.com/shop/shimaleLightArt



SHIMAL'E PELEG LIGHT IN ART

