

## SunBeam • Large Gleams • Tanzania

### Assembly Instructions

#### In the box:

- Ceiling plate
- LED bulbs (are located “inside” the ceiling plate)
- Installation kit - contains spare screws, gloves
- Glasses packed 4 in each bunch (note- labels for size/color)



keep the ‘installation kit’ until you’ve confirmed all components are present

**For USA:** This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.

**For CANADA:** ce produit doit être installé selon le code d’installation pertinent, par une personne qui connaît bien le produit et son fonctionnement ainsi que les risques inhérents.



#### Preparation:

1. Determine your ceiling type (wood, drywall, or concrete) and use the appropriate screws (not provided).  
**For drywall,** locate ceiling joists and make sure the screws go beyond the drywall into the joist.  
**For concrete,** use masonry anchor screws.
2. Familiarize yourself with the installation process by watching the instructional videos provided.  
You can access them using the barcode below.




**Before starting installation, Turn off the relevant electrical power source to ensure safety. !**




#### Installation:

1. Detach the metal bracket from the back of the canopy and mount it onto the ceiling, with the flat side upward. Make sure the electrical wires are exposed near the bracket.



**If your ceiling is sloped, pay attention to the ‘Lower side’/‘Higher side’ labels.**



2. Twist the GND wire coming out of your electrical box with the GND wire of the light fixture. Use the twist connector attached to the GND wire from the bracket.
3. For the next stage you will need a second person to help you hold the fixture up while you connect the electrical wire to the fixture.



**Please wear the gloves provided in order to prevent leaving fingerprints on the canopy.**

4. Lift the main (or upper if two) canopy and hold it close to the bracket while connecting the wires. >>

5. Connect the positive (white) and negative (black) wires from your electrical box with the respective wires from the Fixture. Use the twist connector attached to the wires. It doesn’t matter which wire is positive/negative in this fixture.
6. Carefully position the canopy on to the bracket and fasten it into place using the pre-existing holes.
7. Untie the wires and gently stretch them downwards, repeating the process for each wire. Arrange the wires neatly and plug in the bulbs.
8. Before installing the glasses, make sure to verify that everything is functioning properly.



#### Assembly of glass:

1. Carefully unwrap each glass pack, taking note that each pack contains 2 wide and 2 narrow glasses. Pair them oppositely, starting with the narrow ones, ensuring that the glossy side faces outwards and the matte side faces inwards. If there is any white residue, do not attempt to remove it.
2. Check for arrangement notes provided by the artist regarding pendant size or colors, marked by labels on the glass packs and bulb holder.



**For further guidance, you can watch the instructional video by scanning the QR code provided.**



#### Alignment:

After assembly, if there is any misalignment, grasp the wire an inch above the pendant and pivot it up to 90 degrees to rectify. If gaps remain, consult the video. Follow this method for all pendants.



**For further guidance, you can watch the instructional video by scanning the QR code provided.**

#### Adjustment :

1. To adjust the wire length, locate the small plastic screw within the canopy corresponding to each wire. Carefully rotate it to free the wire, make the necessary adjustments, and then secure it back in place. Handle with caution to prevent any damage.
2. In case of an uneven ceiling, use white or clear silicone to bridge any space between the ceiling and canopy.
3. If your fixture has a double canopy, repeat the installation process for both the upper and lower canopy.

#### Maintenance and Care

1. These Led bulbs are dimmable, with any dimming switch system.
2. **Dust:** Use a soft, dry cloth to regularly dust your fixture.
3. **Metal:** Wipe with a damp mat.

**Note for Future: This fixture incorporates LED GU10 7w 570 lumens 3000K). Always replace with an identical bulb for consistency in performance.**



ENJOY!

WhatsApp: +972-52-5279674 • Email: miri@shimale.co.il  
www.shimale.co.il • www.etsy.com/shop/shimaleLightArt



SHIMALE PELEG  
LIGHT IN ART

